

# PROGRAMMABLE GEN II SOFTENING SYSTEMS

## Single Unit 2" Series



Multi Tank Model 700 Softener Shown

### Multi Tank Standard Features

- Advanced Electronics
- Colored User Alert & Information Screens
- Fiberglass Media Tanks
- Premium Ion Exchange Media
- Pre-programmed & prepared for on site assembly
- Seamless Blow Molded or Rotational Molded Brine Tanks
- Premium Grade Softening Media
- No Hard Water By-Pass
- Pressure Gauge / Sample Valve Ports

### 2" FPT Lead Free Brass Control Valve

- Single Drive Piston Operated
- Soft Water Brine Refill
- NSF / FDA Approved Black Coating
- Auxiliary Operation Options
  - Alarm Relay Output
  - Control up to two separate relay operations
  - Optional No Hard Water Bypass
  - Control Two Separate Auxiliary Valves

### Optional Features

- Electronic Flow Meters
- Salt Monitor & Alarm
- Steel and ASME Tanks
- Choice of Brine Tank Size
- Pumped Brine
- Skid Mounting Pre-Piping
- Custom Tailoring

### Custom Configurations Built to User Requirements

Systems can be built to fit a wide range of user applications  
ASME tanks available on request

## PRODUCT SPECIFICATIONS (per unit)

Model Series	Media Qty Cubic Feet	Grains of Capacity			Flow @ 15 psi drop	Media Tank Dia. x H	Max Drain Flow gpm	Distributor Type
		15lb/ Cubic Feet	10lb/ Cubic Feet	5lb/ Cubic Feet				
300	3	90,000	75,000	60,000	39	14 X 65	4.2	STD
400	4	120,000	100,000	80,000	47	16 X 65	5.3	STD
500	5	150,000	125,000	100,000	53	18 X 65	7.5	STD
700	7	210,000	175,000	140,000	66	21 x 62	9	H&L
1000	10	300,000	250,000	200,000	73	24 x 72	13	H&L
1500	15	450,000	375,000	300,000	84	30 x 72	20	H&L
2000	20	600,000	500,000	400,000	97	36 x 72	25	H&L
3000	30	900,000	750,000	600,000	96	42 x 72	40	H&L
4000	40	1,200,000	1,000,000	800,000	98	48 x 72	50	H&L

### ADDITIONAL OPERATING INFORMATION

For use on potable water only.  
Not intended to be used to treat water that is micro biologically unsafe or of unknown quality.  
Installation must comply with all state and local codes.  
Tank dimensions are based on fiberglass only. Steel tanks dimensions will vary.  
Pressure drops are based on clean media bed. Specifications Subject to Change Without Notice

Operating Water Temperature Range  
Operating Ambient Temperature Range  
Operating Pressure Range  
Electrical Requirements  
Feed Water Turbidity

Max 100°  
Max 120°  
Max 125 psi  
110V-60Hz primary

Minimum 35°  
Minimum 35°  
Minimum 20 psi  
110V-60Hz  
5.0 NTU Max



Aqua Systems Commercial & Industrial • 114 Vista Parkway • Avon, Indiana 46123  
317-272-6715 • 800-997-5492 • Fax 317-272-6728  
www.aquasystemsci.com • e-mail: commercialindustrial@aquasystems.com